

IN THE CLAIMS:

Please amend the claims as follows:

Claims 1 to 44 (Canceled)

45. (Currently Amended) A method of adaptation in point to multipoint communication, the method including steps of:

determining, by a base station, physical and media access control parameters to be used by each of plural customer premises equipment;

packaging said physical and media access control parameters in descriptor packets having a fixed size; and

pre-announcing said physical and media access control parameters to said customer premises equipment by sending said descriptor packets from said base station to said customer premises equipment, with each descriptor packet sent as a first packet in a time division multiple access frame;

determining, by said base station, new physical and media access control parameters to be used by each of said plural customer premises equipment;

packaging said new physical and media access control parameters in new descriptor packets having said fixed size; and

pre-announcing said new physical and media access control parameters to said customer premises equipment by sending said new descriptor packets from said base station to said customer premises equipment, with each new descriptor packet sent as a new first packet in a new time division multiple access frame.

46. (Canceled)

47. (Currently Amended) A method as in claim 45 [[46]], wherein said physical and media access control parameters are in a first layer of an OSI model communication system.

48. (Previously Presented) A method as in claim 47, wherein said step of determining said new physical and media access control parameters is responsive to a higher level layer in said OSI model communication system.

49. (Previously Presented) A method as in claim 48, wherein
said first layer includes a physical layer; and
said higher level layer includes at least one of: a media access layer, a network layer, a transport layer, an application layer.

50. (Currently Amended) A base station for use with point to multipoint communication, comprising:

at least one antenna;
a processor;
program and data memory; and
communication elements that send and receive information over said
communication link using said antenna under control of said processor;
wherein said processor operates under control of instructions stored in said
memory, said instructions including steps of:
determining physical and media access control parameters to be used by each of
plural customer premises equipment;
packaging said physical and media access control parameters in descriptor packets
having a fixed size; and
pre-announcing said physical and media access control parameters to said
customer premises equipment by sending said descriptor packets from said base station to said
customer premises equipment, with each descriptor packet sent as a first packet in a time division
multiple access frame;
determining new physical and media access control parameters to be used by each
of said plural customer premises equipment;
packaging said new physical and media access control parameters in new
descriptor packets having said fixed size; and
pre-announcing said new physical and media access control parameters to said
customer premises equipment by sending said new descriptor packets from said base station to

said customer premises equipment, with each new descriptor packet sent as a new first packet in a new time division multiple access frame.

51. (Canceled)

52. (Currently Amended) A base station as in claim 50 [[51]], wherein said physical and media access control parameters are in a first layer of an OSI model communication system.

53. (Previously Presented) A base station as in claim 52, wherein said step of determining said new physical and media access control parameters is responsive to a higher level layer in said OSI model communication system.

54. (Previously Presented) A base station as in claim 53, wherein
said first layer includes a physical layer; and
said higher level layer includes at least one of: a media access layer, a network layer, a transport layer, an application layer.

55. (Currently Amended) A memory storing information including instructions, the instructions executable by a processor to control a base station for use with point to multipoint communication, the instructions including steps of:

determining physical and media access control parameters to be used by each of plural customer premises equipment;

packaging said physical and media access control parameters in descriptor packets having a fixed size; ~~and~~

pre-announcing said physical and media access control parameters to said customer premises equipment by sending said descriptor packets from said base station to said customer premises equipment, with each descriptor packet sent as a first packet in a time division multiple access frame;

determining new physical and media access control parameters to be used by each of said plural customer premises equipment;

packaging said new physical and media access control parameters in new descriptor packets having said fixed size; and

pre-announcing said new physical and media access control parameters to said customer premises equipment by sending said new descriptor packets from said base station to said customer premises equipment, with each new descriptor packet sent as a new first packet in a new time division multiple access frame.

56. (Canceled)

57. (Currently Amended) A memory as in claim 55 ~~[[56]]~~, wherein said physical and media access control parameters are in a first layer of an OSI model communication system.

58. (Previously Presented) A memory as in claim 57, wherein said step of determining said new physical and media access control parameters is responsive to a higher level layer in said OSI model communication system.

59. (Previously Presented) A memory as in claim 58, wherein
said first layer includes a physical layer; and
said higher level layer includes at least one of: a media access layer, a network layer, a transport layer, an application layer.